

(1) The Different Multislot Classes

Type	Multislot Class	Max No of Receive Timeslots	Max No of Transmit Timeslots	Sum Rx +Tx	T _{ta}	T _{tb}	T _{ra}	T _{rb}
1	1	1	1	2	3	2	4	2
1	2	2	1	3	3	2	3	1
1	3	2	2	3	3	2	3	1
1	4	3	1	4	3	1	3	1
1	5	2	2	4	3	1	3	1
1	6	3	2	4	3	1	3	1
1	7	3	3	4	3	1	3	1
1	8	4	1	5	3	1	2	1
1	9	3	2	5	3	1	2	1
1	10	4	2	5	3	1	2	1
1	11	4	3	5	3	1	2	1
1	12	4	4	5	2	1	2	1
2	13	3	3	N/A	N/A	1 / 0 *)	3	1 / 0 *)
2	14	4	4	N/A	N/A	1 / 0 *)	3	1 / 0 *)
2	15	5	5	N/A	N/A	1 / 0 *)	3	1 / 0 *)

(1) The Different Multislot Classes

Multislot Class Type

Mobile phones with a multislot class of type 1 are not required to transmit and receive at the same time. Opposed to that, mobile phones with a multislot class of type 2 need to support simultaneous transmission and reception (full-duplex). Half-duplex mode of operation is possible (with fixed uplink resource allocation only) for multislot classes 19 – 29 only [2GTS 04.60]. Half-duplex refers to the capability to support either transmission in uplink direction or reception in downlink direction at any given time. Only in half-duplex mode of operation a mobile station with multislot classes 19 – 29 supports the maximum number of timeslots according to its multislot class. Therefore, in half-duplex mode of operation a mobile phone that is currently transmitting is not required to receive anything else than PACCH-information at scheduled times (\Leftrightarrow MEASUREMENT_MAPPING) from the base station. Please note that the fixed uplink resource allocation is becoming an optional feature with GPRS Rel. 99 and GERAN Rel. 4. With GERAN Rel. 5, support for fixed allocation is withdrawn.

Max No of Receive Timeslots / Max No of Transmit Timeslots / Sum

These columns indicate on how many timeslots a mobile phone is capable to transmit and receive per TDMA-frame. Examples for multislot classes 8 and 12 are presented on the following pages. Note that the column „Sum“ presents the aggregated number of allocated transmit and receive timeslots per TDMA-frame that is supported by a mobile phone (see figure)

		TDMA - Frame							
DL	UL	0	1	2	3	4	5	6	7
		5	6	7	0	1	2	3	4

Example: SumRx + Tx = 5
(applicable for MS-Class 10, 11, 12)

Obviously this value is meaningful only for multislot classes 1 to 12.

Reasons:

\Rightarrow Type 2: „Sum“ could be 3 – 6 for multislot class 13, 4 – 8 for multislot class 14 and so on (\Leftrightarrow Ambiguity).

\Rightarrow Type 1: For Multislot classes 19 – 29 there is an either / or relationship of transmit and receive timeslots. Hence the „Sum“ value doesn't make sense.

*) 1 TS with frequency hopping or 0 TS without frequency hopping.

**) 1 TS with frequency hopping or change from receive mode to transmit mode. 0 TS without frequency hopping and no change from receive mode to transmit mode.

***) 1 TS with frequency hopping or change from transmit mode to receive mode. 0 TS without frequency hopping and no change from transmit mode to receive mode.

[2GTS 05.02]

(2) The Different Multislot Classes

Type	Multislot Class	Max No of Receive Timeslots	Max No of Transmit Timeslots	Sum Rx +Tx	T _{ta}	T _{tb}	T _{ra}	T _{rb}
2	16	6	6	N/A	N/A	1 / 0 *)	2	1 / 0 *)
2	17	7	7	N/A	N/A	1 / 0 *)	1	0
2	18	8	8	N/A	N/A	0	0	0
1	19	6	2	N/A	3	1 / 0 **)	2	1 / 0 ***)
1	20	6	3	N/A	3	1 / 0 **)	2	1 / 0 ***)
1	21	6	4	N/A	3	1 / 0 **)	2	1 / 0 ***)
1	22	6	4	N/A	2	1 / 0 **)	2	1 / 0 ***)
1	23	6	6	N/A	2	1 / 0 **)	2	1 / 0 ***)
1	24	8	2	N/A	3	1 / 0 **)	2	1 / 0 ***)
1	25	8	3	N/A	3	1 / 0 **)	2	1 / 0 ***)
1	26	8	4	N/A	3	1 / 0 **)	2	1 / 0 ***)
1	27	8	4	N/A	2	1 / 0 **)	2	1 / 0 ***)
1	28	8	6	N/A	2	1 / 0 **)	2	1 / 0 ***)
1	29	8	8	N/A	2	1 / 0 **)	2	1 / 0 ***)

(2) The Different Multislot Classes

Measurements: Each mobile phone shall perform adjacent cell signal level measurements in 24 out of 26 TDMA-frames. Signal level measurements relate to measuring the BSIC plus the power level of adjacent cells. This rule applies unless the network has provided specific *Measurement Mapping* parameters to the mobile phone that would override this requirement. These *Measurement Mapping* parameters will provide information to the mobile phone at which times, in which timeslots it shall perform adjacent cell measurements [2GTS 04.60]. However, these specific rules only apply in half-duplex mode operation for multislot class 19 – 29 mobile phones. All other mobile phones and multislot classes have to obey the „24 out of 26 TDMA-frames rule“.

Timing Constraints

Being involved in a multislot transmission and / or reception, a mobile phone has to have sufficient time gaps between the allocated timeslots:

⇒ to get ready to receive ($\Leftrightarrow T_{rb}$) and (conditionally) to perform adjacent cell signal level measurements in between ($\Leftrightarrow T_{ra} = T_{rb} + N$ timeslots)

⇒ to get ready to transmit ($\Leftrightarrow T_{tb}$) and (conditionally) to perform adjacent cell signal level measurements in between ($\Leftrightarrow T_{ta} = T_{tb} + K$ Timeslots)

The term „conditionally“ in the previous sentences refers to the fact that a mobile phone will perform adjacent cell signal level measurements either while preparing for transmission or while preparing for reception. Accordingly, the more stringent time constraints T_{ra} and T_{ta} will never apply together during one flow. Rather T_{ra} & T_{tb} will apply together or T_{ta} & T_{rb} will apply together.

Note that in half-duplex mode (only multislot classes 19 – 29) only the less stringent time constraints T_{tb} & T_{rb} may apply together, if the PCU has provided *Measurement Mapping* parameters.

*) 1 TS with frequency hopping or 0 TS without frequency hopping.

**) 1 TS with frequency hopping or change from receive mode to transmit mode. 0 TS without frequency hopping and no change from receive mode to transmit mode.

***) 1 TS with frequency hopping or change from transmit mode to receive mode. 0 TS without frequency hopping and no change from transmit mode to receive mode.


Color Explanation:

- ⇒ MS's with these multislot classes and the according time constraints can be developed, using the dynamic / extended dynamic resource allocation.
- ⇒ MS's with these multislot classes can only be developed with either two antennas or two transceivers.
- ⇒ MS's with these multislot classes cannot operate using neither the dynamic nor the extended dynamic resource allocation method (\Leftrightarrow Time constraints)

[2GTS 04.60 / 2GTS 05.02 / 2GTS 05.08]

Example for Multislot Class 8 to 12

- 4 Receive : 1 Transmit - Configuration



Example for Multislot Class 8 to 12


4 Receive : 1 Transmit - Configuration

The example illustrates a mobile phone with either multislot class 8 or multislot class 12 being involved in a transaction where the mobile phone receives on four timeslots and transmits on one timeslot.

For the determination of T_{ta} , T_{tb} , T_{ra} and T_{rb} the respective timing advance values shall remain unconsidered.


Example for Multislot Class 11 and 12

- 2 Receive : 3 Transmit – Configuration



(1) The Different Network Operation Modes

- The Network Operation Mode is broadcast to the mobile stations in **SYS_INFO13, PACK_SYS_INFO1 and 13**



(1) The Different Network Operation Modes

- **The Network Operation Mode is broadcast to the mobile stations in SYS_INFO13, PACK_SYS_INFO1 and 13**
Three different network operation modes (NOM I, NOM II and NOM III) are defined dependent on whether or not the Gs-interface between SGSN and VLR is available and dependent on whether or not a BTS is equipped with PCCCH.

[2GTS 03.60]

(2) The Different Network Operation Modes

• Network Operation Mode I (NOM I)


CS-Paging and PS-Paging for GPRS Mobile Station **Class A** and **Class B** is done:

=> on PPCH (if configured and only in idle mode)

=> on PCH (if no PPCH is available and only in idle mode)

=> on PACCH (while involved in a packet data transfer)

GPRS-Attach and IMSI-Attach / Location Area Updating and Routing Area Updating are performed in one procedure towards the SGSN (<=> combined)



(2) The Different Network Operation Modes

Network Operation Mode I (NOM I)

In NOM I the Gs-interface [2GTS 09.18] is present and PCCCH may but doesn't need to be equipped. Accordingly the SGSN is in charge not only for the packet-switched paging but also for the circuit-switched paging. The VLR will forward the circuit-switched paging to the SGSN that will relay them on either on PPCH or PCH to the mobile station. Note that the SGSN will use the PPCH also for circuit-switched paging if the PPCH is equipped. It will use the PCH for both types of paging, if there is no PPCH [2GTS 03.60]. In either case the mobile station class A and B is relieved from listening to both, the SGSN and the MSC/VLR for paging. Also, in NOM I only the packet-switched DRX-parameters apply for mobile stations class A and B (and class C in GPRS-attached mode) which is another relieve compared to NOM II.

The NOM I has the major advantage that even a class B mobile station can be alerted of an incoming circuit-switched transaction while involved in a packet-switched transaction. In that case, the circuit-switched paging is forwarded to the mobile station by means of the PACCH [2GTS 03.60]. Note that this advantage does not apply vice versa because paging coordination is possible only from the VLR to the SGSN: Being involved in a circuit-switched transaction, there is no requirement that a mobile station class B still receives the packet-switched paging channel.

Another major advantage of NOM I or rather of an equipped Gs-interface is the possibility to perform attachments and registrations in combined format towards the SGSN. Hence, IMSI- and GPRS-Attach as well as Location Area- and Routing Area-Updating and IMSI- and GPRS-Detachments are done combined [2GTS 03.60 / 2GTS 04.08 / 2GTS 09.18]. It is the responsibility of the SGSN to inform the VLR of any of these procedures.


Note that in NOM I a mobile station will only perform Periodic Routing Area Updating but no Periodic Location Area Updating. It is the responsibility of the SGSN to update the VLR.

Note: Whether or not a mobile station class A/B performs a combined IMSI/GPRS-attachment upon power on also depends on the setup of the mobile station: Some manufacturers prevent automatic GPRS attachment, since there is the possibility that an operator already charges for GPRS attachments.

[2GTS 03.60 / 2GTS 04.08 / 2GTS 09.18]

(6) New Identifiers and Parameters with GMM

- The Ready Timer (T3314)



(6) New Identifiers and Parameters with GMM

The Ready Timer (T3314)

The Ready Timer T3314 is a new timer with GPRS. It is restarted by the mobile station whenever the mobile station has successfully transmitted an LLC-frame. The Ready Timer is restarted by the SGSN for a particular mobile station whenever the SGSN has successfully received an LLC-frame from that mobile station.

- **Default Value of T3314**

The default value of T3314 is 44 s but different values can be negotiated upon GPRS Attachment and Routing Area Updating.


- **T3314 is shorter in the SGSN**

To provide for a synchronous duration of the Ready State in the mobile station and the SGSN the Ready Timer should be configured a little bit shorter (≈ 2 s) in the SGSN to leverage the transfer time of an LLC frame from the mobile station to the SGSN.

[2GTS 04.08 / 2GTS 03.60]

(7) New Identifiers and Parameters with GMM

- Operation of the Ready Timer (T3314)



(7) New Identifiers and Parameters with GMM

Operation of the Ready Timer (T3314)

- **Cell Update Scenario in Ready State**

In Ready State the mobile station will inform the SGSN upon every cell reselection by means of the Cell Update scenario. During the cell update scenario the mobile station will convey a possibly empty LLC-frame to the SGSN which tells the SGSN the Cell ID of the new serving cell of the mobile station. If the cell reselection means also a change of the routing area the mobile station will rather perform a routing area update scenario.

- **No Cell Update Scenario in Standby State**

In Standby State the mobile station will not perform Cell Update scenarios when reselecting the serving cell. However, upon change of the routing area the mobile station in Standby State will still perform Routing Area Updates.

- **Initial Cell Update after GPRS Attach / Routing Area Updating**

If mobile station and SGSN negotiate a specific Ready Timer value either in the GPRS Attach- or the Routing Area Update-procedure the mobile station will immediately perform a cell update scenario by responding to the ATT_ACC- / RA_UPD_ACC-message with a ATT_COM- / RA_UPD_COM-message.

The only exceptions to this rule apply if the SGSN has set T3314 = 0 or if the SGSN has indicated *Force to Standby* (⇔ information element).


Please compare the Ready Timer to the screen saver timer on your computer.

Note: The Ready Timer has no impact on the DRX behavior of the mobile station [2GTS 03.64]. When the mobile station is not transmitting or receiving (no TBF is activated) it will change into the negotiated DRX mode of operation. If DRX is applied, the mobile station will listen only to its paging channel(s) even while the Ready Timer is running.

[2GTS 04.08 / 2GTS 03.60]

(8) New Identifiers and Parameters with GMM

- Implications of the Ready Timer: Reduction of the Paging Load



(8) New Identifiers and Parameters with GMM

Implications of the Ready Timer:

Reduction of the Paging Load

If a mobile station is in Ready State, the SGSN is not only aware of the routing area in which the mobile station is currently located but it even knows the very cell that is currently serving the mobile station.


Consequently, while a mobile station is in Ready State, the size of the necessary paging area shrinks down to just the serving cell. As a matter of fact, there won't even be a packet-switched paging procedure required while a mobile station is in Ready State as will be explained on the following page.

However, in case of NOM I and for a mobile station class A or B in Ready State, circuit-switched paging will be performed only in the cell. Therefore, the paging load is reduced.

Reduction of the paging load is particularly important for any kind of bursty traffic in downlink direction.

(9) New Identifiers and Parameters with GMM

- Implications of the Ready Timer: Reduction of the Paging Time



(9) New Identifiers and Parameters with GMM

Implications of the Ready Timer

Reduction of the Paging Time

For any kind of packet-switched traffic, the latency shall be as small as possible. Consider a bursty application transmitting data in downlink direction to a mobile station. It would be annoying, if the network (\Leftrightarrow the SGSN) would need to page the mobile station each time to resume transmission. This was the primary reason for the introduction of the Ready Timer:


- \Rightarrow As long as the Ready Timer is running, packet-switched paging is not necessary. Instead, the SGSN will just forward the respective LLC-PDU's to the PCU (embedded in BSSGP DL-UNITDATA PDU's) and implicitly request the PCU to establish a downlink TBF (resource allocation) to the mobile station. The time delay between a downlink data packet arriving at the SGSN and being forwarded to the mobile station is minimized.
- \Rightarrow If the mobile station is in Standby State, the SGSN only knows the routing area in which the mobile station is currently registered. Accordingly, the SGSN first needs to send BSSGP PAGING-PS-PDU's to all PCU's which serve cells of this routing area. If the mobile station receives the paging message in one of these cells it needs to establish an uplink TBF to transmit an empty LLC-frame to the SGSN to consequentially move into Ready State. This procedure, paging and paging response will cause an additional delay time.

Note: There is no explicit page response message defined in GPRS neither for GMM nor for RLC/MAC. Paging response is achieved similarly to cell updating through the transfer of an empty LLC-frame (SAPI = '1') to the SGSN which moves the mobile station back into Ready State.


(10) New Identifiers and Parameters with GMM

- (c) Specific Settings of the Ready Timer (T3314)

$T3314 = ,111X\ XXXX'_{bin}$



$T3314 = ,XXX0\ 0000'_{bin}$



(10) New Identifiers and Parameters with GMM

(c) Specific Settings of the Ready Timer (T3314)

Bit 7, 6 and 5 of the 8 bit long generic GMM Timer information element encoding indicate the unit type of the respective timer (e.g. Ready Timer) [2GTS 04.08]:


Bit Coding (bin)	Unit Type
000	2 seconds
001	1 minute
010	1/10 hour
111	Deactivated
All others	To be interpreted as '001'

Bit 4 to 0 contain the requested value of T3314 (\Leftrightarrow if sent by the mobile station) or the value of T3314 to be applied (\Leftrightarrow if sent by the SGSN).

- **T3314 = ,111 XXXX' _{bin} (deactivated \Rightarrow No Standby State)**
In the deactivated state the Ready Timer is neither started nor stopped. The Ready State never ends which means that mobile station and SGSN will never move into Standby State.
- **T3314 = ,XXX 00000' _{bin} (Ready Timer to be stopped immediately \Rightarrow No Ready State)**
If the Ready Timer value is set to ,00000' _{bin} then T3314 is to be stopped immediately. Mobile station and SGSN remain in Standby State even after an LLC-frame transmission by the mobile station. Both, mobile station and SGSN will never move into Ready State.

Note: Even in packet idle mode the mobile station will remain in Non-DRX mode after data transmission or data reception for a time period defined by the parameter NON-DRX-TIMER (0 ... 64 s) which is part of the DRX parameter information element. This information element is sent by the mobile station to the SGSN as part of the ATT_REQ-message (\Leftrightarrow mandatory) and / or the RA_UPD_REQ-message (\Leftrightarrow optional).


Practical Exercise:



"Please interpret these Ready Timer Values"



(1) One-Phase Packet Access on PCCCH in Detail



(1) One-Phase Packet Access on PCCCH in Detail

Initial Conditions

The network operates in NOM I or III, the Mobile Station is Class A, B or C and may or may not be already attached to circuit-switched and packet-switched services. The RLC/MAC-layer receives the request from LLC or GMM to transmit one or more PDU's to the network.

Applicability of this Procedure


- ⇒ One-Phase Packet Access on PCCCH is applicable only in case of acknowledged RLC/MAC operation mode. However, the Short Access, the Access for GMM/SM and the Access for Cell Update will deploy the same procedure as One-Phase Packet Access.

Description

- ⇒ The mobile station will start T3186 (\Leftrightarrow 5 s) when it sends the first PACK_CHAN_REQ-message [*Access Reason (m)*, *Random Reference (m)*] on its PCCCH timeslot (as given by the parameter PCCCH_GROUP) to the BTS. The mobile station may send max. (MAX_RETRANS + 1) PACK_CHAN_REQ- to the BTS. The number of TDMA-frames between the single PACK_CHAN_REQ-messages depends on the number of PRACH-blocks on this timeslot, on the parameters TX_INT and S which are like MAX_RETRANS broadcast in the PRACH_CONTROL_PARAMETERS in PACK_SYS_INFO1 and on the Persistence Level (0 ... 15) (\Leftrightarrow also part of the PRACH_CONTROL_PARAMETERS) which depends on the Radio Priority that the mobile station may apply. If T3186 expires before the mobile station could transmit (MAX_RETRANS + 1) PACK_CHAN_REQ-messages then a packet access failure needs to be reported and the mobile station returns to packet idle mode.
- ⇒ Having send the last PACK_CHAN_REQ-message the mobile station will start T3170 (\Leftrightarrow (TX_INT + 2S) TDMA-frames [in seconds]).
- ⇒ Mobile stations class A or B shall continue to listen for their PPCH (\Leftrightarrow NOM I) or PCH (\Leftrightarrow NOM II / NOM III) to be able to respond to a circuit-switched paging command message. Class B mobile stations may abort the One-Phase Packet Access procedure when receiving a circuit-switched paging.
- ⇒ Having received the PACK_CHAN_REQ-message from the mobile station the BTS will forward it to the PCU within a normal PCU-frame. The PCU will build a PACK_UL_ASS-message [*Page_Mode (m)*, {*Global TFI / TLLI / TQI / Random Reference*}(m), *Coding Scheme (m)*, *Coding Scheme for TLLI (m)*, *Packet Timing Advance (m)*, *Frequency Parameters (o)*, {*Dynamic / Fixed / Single Block Allocation*}(m)] and send it to the mobile station on PAGCH.
- ⇒ Having received the PACK_UL_ASS-message the mobile station will stop T3170, react upon the allocation and start T3164 (\Leftrightarrow 5 s) if the dynamic resource allocation method is used.

[2GTS 04.60]

(2) One-Phase Packet Access on PCCCH in Detail



(2) One-Phase Packet Access on PCCCH in Detail


Description

- ⇒ With T3164 (⇔ 5 s) running the mobile station waits for the allocation to begin.
- ⇒ Upon sending of the first RLC-Data Block [⇔ *including the TLLI of the mobile station for contention resolution*] the mobile station will set N3104 = 1 stop T3164 and start T3166 (⇔ 5 s).
- ⇒ With every new RLC-Data Block [⇔ *including the TLLI of the mobile station for contention resolution*] that the mobile station sends N3104 is incremented.
- ⇒ When the PCU receives the first RLC/MAC-Data Block [⇔ *including the TLLI of the mobile station for contention resolution*] it will issue a PACK_UL_ACK-message [*Page_Mode (m), Uplink TFI (m), Coding Scheme (m), Ack/Nack-Description (m), Cont. Resolution TLLI (o), Packet Timing Advance (o), Power Control Parameters (o), Fixed Allocation Parameters (o)*] to the mobile station.
- ⇒ If the PACK_UL_ACK-message contains the related Uplink TFI and the TLLI of the mobile station the contention resolution procedure was successful and the mobile station may continue to send RLC-Data Blocks without including the TLLI. The mobile station shall stop T3166 and reset counter N3104.
- ⇒ If the PACK_UL_ACK-message contains the related Uplink TFI but not the TLLI of the mobile station the contention resolution procedure was not successful. Consequently, the mobile station shall immediately stop to use the allocated resources and may retry the packet access procedure.

On PCCCH the chances to send PACK_CHAN_REQ-messages to the PCU depend on the Radio Priority (⇔ QoS-profile) of the TBF to be established. Besides, on PRACH with 11 bit format the mobile station can convey its radio priority already in the access burst, if important (⇔ signaling procedures for GMM, SM and Cell Update or RLC/MAC-control anyway shall use the highest radio priority).

[2GTS 04.60]

(1) Two-Phase Packet Access on PCCCH in Detail



(1) Two-Phase Packet Access on PCCCH in Detail

Initial Conditions

The network operates in NOM I or III, the Mobile Station is Class A, B or C and may or may not be already attached to circuit-switched and packet-switched services. The MAC-layer receives the request from RLC to transmit an RLC/MAC-control message (e.g. PACK_MEAS_REP) or to transmit one or more LLC-PDU's in acknowledged or unacknowledged RLC/MAC operation mode.

Applicability of this Procedure


- ⇒ Two-Phase Packet Access is mandatory in case of unacknowledged RLC/MAC operation mode and if an RLC/MAC-control message shall be transmitted. Two-Phase Packet Access may be used in case of acknowledged RLC/MAC operation mode.

Description

- ⇒ The mobile station will start T3186 (\Leftrightarrow 5 s) when it sends the first PACK_CHAN_REQ-message [*Access Reason (m)*, *Random Reference (m)*] on its PCCCH timeslot (as given by the parameter PCCCH_GROUP) to the BTS. The mobile station may send max. (MAX_RETRANS + 1) PACK_CHAN_REQ- to the BTS. The number of TDMA-frames between the single PACK_CHAN_REQ-messages depends on the number of PRACH-blocks on this timeslot, on the parameters TX_INT and S which are like MAX_RETRANS broadcast in the PRACH_CONTROL_PARAMETERS in PACK_SYS_INFO1 and on the Persistence Level (0 ... 15) (\Leftrightarrow also part of the PRACH_CONTROL_PARAMETERS) which depends on the Radio Priority that the mobile station may apply. If T3186 expires before the mobile station could transmit (MAX_RETRANS + 1) PACK_CHAN_REQ-messages then a packet access failure needs to be reported and the mobile station returns to packet idle mode.
- ⇒ Having send the last PACK_CHAN_REQ-message the mobile station will start T3170 (\Leftrightarrow (TX_INT + 2S) TDMA-frames [in seconds]).
- ⇒ Mobile stations class A or B shall continue to listen for their PPCH (\Leftrightarrow NOM I) or PCH (\Leftrightarrow NOM II / NOM III) to be able to respond to a circuit-switched paging command message. Class B mobile stations may abort the One-Phase Packet Access procedure when receiving a circuit-switched paging.
- ⇒ Having received the PACK_CHAN_REQ-message from the mobile station the BTS will forward it to the PCU within a normal PCU-frame. The PCU will build a PACK_UL_ASS-message [*Page Mode (m)*, {*Global TFI / TLLI / TQI / Random Reference*}(m), *Coding Scheme (m)*, *Coding Scheme for TLLI (m)*, *Packet Timing Advance (m)*, *Frequency Parameters (o)*, {*Dynamic / Fixed / Single Block Allocation*}(m)] and send it to the mobile station on PAGCH.
- ⇒ Having received the PACK_UL_ASS-message the mobile station will stop T3170 and react upon the allocation.

[2GTS 04.60]

(2) Two-Phase Packet Access on PCCCH in Detail



(2) Two-Phase Packet Access on PCCCH in Detail

Description

- ⇒ The mobile station will wait until the indicated uplink radio block occurs (⇔ Starting Time) and use this uplink radio block to transmit an RLC/MAC-control message (e.g. `PACK_RES_REQ` [*Access Type* (o), {*Global TFI* / **TLLI**} (m), *MS Radio Access Capability* (o), *PEAK_THROUGHPUT_RATE* (m), *RADIO_PRIORITY* (m), *RLC_MODE* (m), *LLC_PDU_TYPE* (m), *RLC_OCTET_COUNT* (m), *Change_Mark* (o), *C_Value* (m), *Sign_Var* (o), *I_Level_TS 0 – 7* (o)] to the network. If the message sent is `PACK_RES_REQ`, the mobile station will start T3168 (⇔ as broadcast in `SYS_INFO13`, `PACK_SYS_INFO1` and `PACK_SYS_INFO13` / GPRS Cell Options Information Element).
- ⇒ Having received the `PACK_RES_REQ`-message the PCU will (if possible) allocate appropriate resources and convey a `PACK_UL_ASS`-message [*Page_Mode* (m), {*Global TFI* / **TLLI** / *TQI* / *Random Reference*} (m), *Coding Scheme* (m), *Coding Scheme for TLLI* (m), *Packet Timing Advance* (m), *Frequency Parameters* (o), {*Dynamic* / *Fixed* / *Single Block Allocation*} (m)] to the mobile station. Upon reception of `PACK_UL_ASS` the mobile station will stop T3186 and react upon the allocation.
- ⇒ If the `PACK_UL_ASS`-message contains the related Uplink TFI and the TLLI of the mobile station the contention resolution procedure was successful.
- ⇒ Note that in case of Two-Phase Packet Access the mobile station will not include its TLLI in the RLC-Data Blocks that are sent.

[2GTS 04.60]

Practical Exercise:


*“Was it One-Phase Access
or Two-Phase Access ?”*

BITMASK	ID Name	Comment or Value
00-----	Payload Type	RLC Data Block
--0010--	Countdown Value	2
-----0-	Stall Indicator	MS RLC Tx Window is not stalled
-----0	Retry	MS sent CHN_REQ msg once
00-----	Spare	0
--00000-	Temporary Flow Identifier	0
-----1	TLLI Indicator	TLLI Field is present
0000000-	Block Sequence Number	0
-----1	Extention bit	No ext. octets follows
B4	TLLI	c1c55555
B20*	RLC Data Block #1	0b c1 f1 65 00 00 7c 45 00 00 3c ...

HEX	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
0	01	00	39	02	08	01	01	c1	c5	55	55	0b	c1	f1	65	00
10	00	7c	45	00	00	3c	c9	35	00	00	20	01	99	12	0a	64
20	00	02	0a	00	24	25	25	cf								



(1) The Dynamic Resource Allocation Method



(1) The Dynamic Resource Allocation Method

The dynamic resource allocation method is based on the 3 bits long USF (Uplink State Flag) which is part of every downlink RLC-data and control block. On an assigned timeslot N, the USF of downlink block K allocates uplink block (k+1) to the mobile station that has been allocated this USF for this timeslot.

Frequently, there is the question about the differences between USF and TFI. As a matter of fact, there is several differences between these two identifiers:


- ⇒ Most importantly, the TFI serves as identifier for all data packets in either direction which belong to one data flow while the USF is just denoting the user of the next uplink radio block.
- ⇒ The TFI is applicable to all timeslots which are used for a given data transfer while the USF is applicable to a single timeslot only.
- ⇒ The TFI is a mandatory parameter while the USF is only required for dynamic allocation.

Note: If the PCU has no downlink blocks to transmit it will use PACK_DL_DUMMY_CTRL_BLK-messages as bearers of the USF.

Note: On every timeslot the PCU shall reserve a USF-Unused-Value for identifying radio blocks for uplink PACCH or radio blocks that are used for fixed allocations. There is no fix value defined for the USF-Unused-Value. On timeslots with PCCCH the USF-Free-Value = '111'bin shall be reserved in addition for denoting of PRACH blocks. Consequently, there are 7 USF-values available for dynamic and extended dynamic resource allocations on timeslots without PRACH while on timeslots that deploy PRACH, there is only 6 USF-values available for this task.

[2GTS 04.60]

(2) The Dynamic Resource Allocation Method



(2) The Dynamic Resource Allocation Method

For the operation of dynamic resource allocations different timers and counters are in operation on the mobile station side and in the PCU.

- ⇒ The PCU will increment N3101 with every USF-allocation to a certain mobile station. If the respective uplink RLC-data block is received from that mobile station the PCU will reset N3101.
- ⇒ If multiple USF-allocations result in no RLC-data block being received from that mobile station and $N3101 = N3101_{\max} (> 8)$, then the PCU will stop scheduling uplink resources for that mobile station and start timer T3169 ($\Leftrightarrow \geq 5 \text{ s}$). If T3169 expires and the mobile station has not resumed the uplink TBF the PCU may reuse the TFI and USF.
- ⇒ On the other hand, the mobile station will start T3180 ($\Leftrightarrow 5 \text{ s}$) with every “own” USF-value that is received on one of the allocated timeslots. If T3180 expires which means that the mobile station didn't receive a block allocation, the mobile station shall perform an abnormal release and perform another packet access procedure.

[2GTS 04.60]

PACK_UL_ASS-Message with Dynamic Allocation

```

+-----+-----+-----+
|Packet Uplink Assignment|
|01-----|Payload Type|RLC/MAC Control Block, no opt.octets|
|--00----|Relative Reserved Block Period|TDMA frame N+13|
|----0---|Supplementary/Polling|RRBP field is not valid|
|-----000|Uplink State Flag|0|
|001010--|Message Type|10|

```

```

3 Dynamic Alloc Struct
0-----|Extended Dynamic Allocation|Dynamic Allocation|
-0-----|Bit|0|
--0-----|USF Granularity|Transmit 1 RLC/MAC block|
---1-----|Bit|1|
***b5***|Uplink TFI assignment|0|
-0-----|Bit|0|
--0-----|Bit|0|
---1-----|Bit|1|
----0011|Alpha|alpha = 0.3|
0-----|Bit|0|
-0-----|Bit|0|
--1-----|Bit|1|
---100--|USF TN2|4|
***b5***|GAMMA TN2|3|
---1-----|Bit|1|
---000--|USF TN3|0|
***b5***|GAMMA TN3|3|
---1-----|Bit|1|
---111--|USF TN4|7|
***b5***|GAMMA TN4|3|
-----0--|Bit|0|
-----0--|Bit|0|
-----0--|Bit|0|
3 (end of) Dynamic Alloc Struct

```

No extended dynamic allocation

USF-Granularity Flag = 0. Therefore USF is valid for only one radio block.

Different USF-values per timeslot

PACK_UL_ASS-Message with Dynamic Allocation

In case of dynamic allocation the PACK_UL_ASS- or PACK_TS_RECONF-message will contain:

- ⇒ The information whether EXTENDED_DYNAMIC_ALLOCATION (m) shall be applied.
- ⇒ The information whether or not downlink power control is used and what the offset downlink power level (P0 (o)) relative to BCCH is.
- ⇒ The information which power reduction mode shall be used for this TBF (PR_MODE (o)) (⇔ only if downlink power control is used).
- ⇒ The information whether USF-detection authorizes the mobile station to transmit only in the next or in the next four uplink radio blocks on this timeslot (USF_GRANULARITY) (m).
- ⇒ The assignment of the uplink TFI (o)
- ⇒ The possible limitation of a TBF. By means of RLC_DATA_BLOCKS_GRANTED (o) the mobile station can be limited to transfer only the indicated number of uplink radio blocks.
- ⇒ The delay between the assignment message and the allocation (TBF_STARTING_TIME (o))
- ⇒ The USF (m) per timeslot number plus the information of the uplink power control parameters (ALPHA (o) and GAMMA (o). Note that GAMMA is included per timeslot.

(m) ⇒ mandatory parameter

(o) ⇒ optional parameter

(c) ⇒ parameter is present under certain conditions


[2GTS 04.60]

Practical Exercise:

“How much time does a mobile station have after USF-detection on TS 3 to prepare for transmission ?”

Timeslots

Last Segment of
Downlink Block K



■ **Index:**

2

26-Multiframe	56
---------------------	----

5

51-Multiframe	56
52-Multiframe	56, 58

A

A5/X	640
Abis-Interface	8
A-bit	666
A-Bit	576
ABM	644
AC-Bit	488
Access for Cell Update	342
Access Mechanisms on CCCH	316
Access Point Name	250
ACCESS_BURST_TYPE	342
Address Control Bit	488
ADM	642
A-Interface	8
Alignment Octets	576
ALLOCATION_BITMAP	362
ALLOCATION_BITMAP_LENGTH	362
ALPHA	420
APN	250

AT-commands	38
ATT_ACC	152, 170
ATT_COM	152, 170
ATT_REJ	152
ATT_REQ	152, 166
AUTH_CIPH_REJ	156
AUTH_CIPH_REQ	156, 168
AUTH_CIPH_RSP	156, 168
Auxiliary TLLI	130

B

Bc	534
Be	534
BECN	528, 536
BG	40
B-Interface	8
Block Coding	96
Block Period	362
Block Sequence Number	478
BLOCKS_OR_BLOCK_PERIODS	362
B _{max}	612
B _{max} default MS	614
Border Gateway	40
BS_CV_MAX	386
BS_PAG_BLKs_RES	68
BS_PBCCH_BLKs	66
BS_PCC_CHANS	66
BS_PRACH_BLKs	66
BSC	6

BSIC.....	58
BSN.....	386, 478
BSN'.....	386
BSS.....	6
BSSAP+-GPRS-DETACH-ACK.....	190
BSSAP+-GPRS-DETACH-IND.....	190
BSSAP+-IMSI-DETACH-ACK.....	188
BSSAP+-IMSI-DETACH-IND.....	188
BSSAP+-LOCATION-UPDATE-ACCEPT.....	172
BSSAP+-LOCATION-UPDATE-REQUEST.....	172
BSSAP+-TMSI-REALLOCATION-COMPLETE.....	174, 180
BSSGP.....	566
BSSGP Blocking Procedure.....	604
BSSGP DL-UNITDATA PDU.....	576
BSSGP Flush Logical Link Procedure.....	606
BSSGP PDU-Types.....	622
BSSGP Reset Procedure.....	602
BSSGP UL-UNITDATA PDU.....	586
BSSGP Unblocking Procedure.....	604
BSSGP Virtual Connection.....	540
BSSGP Virtual Connection Identifier.....	540
BTS.....	6
BTS_PWR_CTRL_MODE.....	362
bucket leak rate.....	612
bucket size.....	612
BVC.....	540
<i>BVC Measurement</i>	614
BVC-BLOCK.....	628
BVC-BLOCK-ACK.....	604, 628
BVC-BLOCK-message.....	604
BVC-BLOCK-RETRIES.....	604
<i>BVC-Bucket Size</i>	614
BVCI.....	540, 542, 574
BVC-RESET.....	628
BVC-RESET-ACK.....	628

BVC-RESET-ACK-message.....	602
BVC-RESET-message.....	602
BVC-UNBLOCK.....	628
BVC-UNBLOCK-ACK.....	604, 630
BVC-UNBLOCK-message.....	604
BVC-UNBLOCK-RETRIES.....	604

C

C.....	614
C value.....	418
C/R-Bit.....	528, 576, 664
Cell Identity.....	586
Cell Reselection.....	380
Cell Update.....	136
Cell Update Procedure.....	176
CELL_RESELECT_HYSTERESIS.....	124
CHAN_REQ.....	318
CHAN_RQD.....	318
<i>Channel Quality Report</i>	340
<i>Channel Request Description</i>	340
Charging (foreign network resources).....	36
Charging (own network resources).....	26
CI.....	586
C-Interface.....	8
ciphering.....	22, 648
CIR.....	534
Circuit-switched paging.....	590
Closed Loop Power Control.....	420
close-ended TBF.....	358
Coding Schemes 1 - 4.....	94
Command / Response-Bit.....	664
Compression in SNDCP.....	704
Cont. Resolution TLLI.....	320
contention resolution procedure.....	314

Continuous Timing Advance Update Procedure.....	74
CONTROL_ACK_TYPE	384
Convolutional Coding.....	96, 98
countdown procedure	386
Countdown Value	382, 466
CS-1.....	96
CS-2.....	98
CS-3.....	98
CS-4.....	102
CSN.1	306
CV	382, 466

D

Data Compression (\Leftrightarrow V.42bis).....	28
D-Bit.....	497
DCOMP.....	706
DE-Bit.....	528, 532
Definition of a PLMN	6
DEL_PDP_CT_REQ.....	188
DEL_PDP_CT_RSP	188
Delay Class.....	232
DET_ACC	152, 190
DET_REQ.....	152, 188
DHCP.....	38, 286
D-Interface	8
Direction Bit	497
DLCI.....	526, 528
DL-UNITDATA	622
DL-UNITDATA PDU	576
Downlink Power Control	424
Downlink power control mode A	428
Downlink power control mode B	430
Downlink Resource Allocation	360
Downlink TBF Operation.....	402

DOWNLINK_CONTROL_TIMESLOT	362
DRX	136, 590
DRX parameter information element.....	142
dynamic allocation of uplink resources.....	364

E

EA-Bit	528
E-bit	676
E-Bit.....	482
E-Interface	8
encryption	648
Extended Dynamic allocation of uplink resources.....	374
EXTENDED_DYNAMIC_ALLOCATION	374
Extension-Bit	482

F

FBI-Bit.....	392, 468
F-bit	678, 706
FCS	528, 658
<i>Feature bitmap</i>	602
FECN.....	528, 536
Final Block Indicator Bit.....	392, 468
Final Segment Bit	490
<i>Final Ack Indication</i>	388
FINAL_ALLOCATION	362
F-Interface	8
fire code.....	96
Fixed Allocation of uplink resources.....	362
flag.....	528
Flow Control on the Gb-Interface	612
FLOW-CONTROL-BVC.....	630
FLOW-CONTROL-BVC-ACK	630
FLOW-CONTROL-BVC-message.....	614

FLOW-CONTROL-MS	630
FLOW-CONTROL-MS-ACK	630
<i>Flush Action</i>	606
Flush Logical Link Procedure	606
FLUSH-LL	632
FLUSH-LL-ACK	632
FLUSH-LL-ACK-message	606
FLUSH-LL-message	606
<i>Force to Standby</i>	136
Foreign TLLI	130
Frame Check Sequence	658
FS-Bit	490

G

Ga-interface	10
Gamma	418
Gateway-MSC	6
Gb-interface	10
Gc-interface	10
Gd-Interface	10
GEA/1	648
GGSN	32
Gi-Interface	10
G-Interface	8
Global TFI	358
GMM	18, 566
GMM Timer information element encoding	142
GMM_INFO	156
GMM_STATUS	156
G-MSC	6
Gn-interface	10
Gp-interface	10
GPRS Resumption IE	592
GPRS SUSPENSION REQUEST	592

GPRS_MS_TXPWR_MAX_CCH	416
GPRS-INDICATOR	64, 124
Gr-interface	10
Gs-interface	10, 88, 172, 178

H

HALF_DUPLEX_MODE	362
Half-duplex mode of operation	48
HDLC	658

I

IDENT_REQ	156, 166
IDENT_RSP	156, 166
IDLE-State	120
IHOSS	248
IMEI-check	168
IMM_ASS_CMD	318
implicit detach	148
Input Offset Value	648
input variable	648
Interleaving	96, 98, 102
interleaving in GPRS	94
Interworking Function	6
IOV	648
IOV-I	688
IOV-UI	688
IPCP	286
IWF	6

K

k	666
Kc	648

KC	66
kD	666, 690
kU	666, 690

L

L(p)	612
LAC	124
LAI	124
Legend	160
Length Indicator-Field	482
LI-Field	482
LLC	638
LLC ACK-frame	672
LLC DISC-frame	678
LLC DM-frame	682
LLC FRMR-frame	684
LLC I+S-frame	666
LLC RNR-frame	670
LLC RR-frame	668
LLC SABM-frame	678
LLC SACK-frame	674
LLC UA-frame	678
LLC UI-frame	676
LLC XID-frame	686
LLC_PDU_TYPE	340
LLC-DISCARDED	632
LLC-Version Number	688
Local TLLI	130
location area	122
LSA-Information	576

M

MAC	312
-----------	-----

MAP cancelLocation-procedure	170
MAP insertSubscriberData-procedure	184
MAP purgeMS-procedure	190
MAP updateGprsLocation procedure	170
MAX_RETRANS	318
M-bit	706
M-Bit	482
MCC	124
mD	690
Mean Throughput Class	234
Measurement Mapping parameters	50
MEASUREMENT_MAPPING	362
measurements	50
Medium Access Control	312
Message Format for GMM and SM	150
MNC	124
Mobile Reachable Timer	146
Mobile Station Class A	42
Mobile Station Class B	44
Mobile Station Class C	46
Mobile Terminating PDP Context Activation	280
More-Bit	482
MS_TXPWR_MAX_CCH	416
MS-Radio Access Capability	576, 580
mU	690
Multislot Class Type	48
Multislot Classes	48

N

N(R)	668, 678
N(S)	666, 678
N200	678, 688
N201	666
N201-I	666, 688

N201-U.....	688
N202	676
N3101	366
N3102	406, 410
N3103	388, 390
N3104	320
N3104_MAX	320
N3105	402
NC0.....	380
NC1.....	380
NC2.....	380
Network Control Order.....	380
Network Operation Mode.....	86
Network Operation Mode I.....	88
Network Operation Mode II.....	90
Network Operation Mode III.....	92
Network Service – Virtual Connection Group	540
Network Service Entity.....	540
Network Service Entity Identifier.....	540
Network Switching Subsystem	6
NM	566
NOM I.....	88
NOM II.....	90
NOM III.....	92
Non-DRX mode	142
NON-DRX-TIMER.....	142
Non-Transparent Access	38
N-PDU.....	702
N-PDU number	706
NS Link Establishment.....	548
NS Link Test	554
NS-ALIVE	546
NS-ALIVE-ACK.....	546
NS-ALIVE-RETRIES.....	558
NSAPI	714

NS-BLOCK	544
NS-BLOCK-ACK.....	544
NS-BLOCK-RETRIES	544
NSE	540
NSEI	540, 574
NS-RESET	544
NS-RESET-ACK.....	544
NSS	6
NS-STATUS	546
NS-UNBLOCK.....	546
NS-UNBLOCK-ACK	546
NS-UNBLOCK-RETRIES	546
NS-UNITDATA	544
NS-VC	538
NS-VCG.....	540
NS-VCI	538
NS-VL.....	538
Null Routing Area	122

O

octet stream protocol	248
One-Phase Packet Access.....	314
One-Phase Packet Access on CCCH in Detail	318
Open Loop Power Control.....	420
open-ended TBF	358
Operation of the PACCH during an Uplink TBF	72
Ordered List of Blocks	58
OSP	248
OVERFLOW COUNTER	654

P

P0	362, 428
PACCH	72

PACK_ACC_REJ.....	506	Packet Common Control Channel.....	66
PACK_CELL_CHANGE_FAIL.....	504	Packet Data Traffic Channel.....	70
PACK_CELL_CHANGE_ORDER.....	506	Packet Notification Channel.....	68
PACK_CHAN_REQ.....	348, 504	Packet Paging Channel.....	68
PACK_CTRL_ACK.....	384, 504	Packet Random Access Channel.....	66
PACK_DL_ACK.....	394, 402, 504	Packet Timing Advance Control Channel.....	72
PACK_DL_ASS.....	506	PACKET TIMING ADVANCE Information Element.....	76
PACK_DL_DUMMY_CTRL_BLK.....	510	Packet-switched paging.....	120, 590
PACK_MEAS_ORDER.....	508	PAGCH.....	68
PACK_MEAS_REP.....	504	PAGING-CS.....	624
PACK_MOBILE_TBF_STAT.....	506	PAGING-PS.....	624
PACK_PAG_REQ.....	508	PAN_DEC.....	408, 410
PACK_PDCH_REL.....	508	PAN_INC.....	406, 410
PACK_POLL_REQ.....	508	PAN_MAX.....	406, 410
PACK_PRACH_PARAM.....	508	Parity & Tail Bits.....	98, 102
PACK_PSI_STAT.....	506	Payload Type Field.....	460
PACK_PWR_CON_TA.....	508	P _b	422
PACK_PWR_CTRL_TA.....	84	PBCCH.....	66
PACK_QUEUING_NOT.....	510	PBCCH and/or PCCCH on 51-Multiframe.....	64
PACK_RES_REQ.....	340, 506	P-bit.....	678
PACK_SYS_INFO1.....	512	PC_MEAS_CHAN.....	422
PACK_SYS_INFO13.....	512	PCCCH.....	66
PACK_SYS_INFO2.....	512	PCOMP.....	706
PACK_SYS_INFO3.....	512	PCU.....	12
PACK_SYS_INFO3bis.....	512	PCU-Frames.....	12
PACK_SYS_INFO4.....	512	PD.....	150
PACK_SYS_INFO5.....	512	PD-Bit.....	664
PACK_TBF_REL.....	510	PDCH.....	62
PACK_TS_RECONF.....	360, 510	PDTCH.....	70
PACK_UL_ACK.....	320, 388, 390, 510	PDU-lifetime.....	576
PACK_UL_ASS.....	318, 510	Peak Throughput Class.....	236
PACK_UL_DUMMY_CTRL_BLK.....	388, 504	PEAK_THROUGHPUT_RATE.....	340
Packet Access Grant Channel.....	68	Periodic Routing Area Updating Timer.....	146
Packet Associated Control Channel.....	72	Persistence Level.....	348
Packet Broadcast Control Channel.....	66	P _{max}	416

PM-bit.....	676
PNCH.....	68
Power control.....	414
Power Reduction Field.....	476
PPCH.....	68
PR mode A.....	432
PR mode B.....	432
PR_MODE.....	362
PRACH.....	66
PRACH_CONTROL_PARAMETER.....	348
Precoding of the first 3 Bits of the MAC-Header.....	98, 102
PR-Field.....	424, 476
Priority.....	576
protected mode.....	676
Protocol Discriminator.....	150
PTCCH.....	72
PTCCH/D.....	80
PTCCH/U.....	74
P-TMSI.....	128
P-TMSI Signature.....	128
P-TMSI_REAL_CMD.....	154
P-TMSI_REAL_COM.....	154
PTM-UNITDATA.....	622
Puncturing.....	98, 100
PVC.....	526

Q

QoS.....	664
QoS-profile.....	226, 576, 586
Quality Based Power Control.....	420

R

R.....	612
--------	-----

<i>R_default_MS</i>	614
RA Color Code.....	124
RA_RESELECT_HYSTERESIS.....	124
RA_UPD_ACC.....	154
RA_UPD_COM.....	154, 180
RA_UPD_REJ.....	154
RA_UPD_REQ.....	154, 178
RAC.....	124
RA-CAPABILITY.....	622
RA-CAPABILITY-UPDATE.....	624
RA-CAPABILITY-UPDATE-ACK.....	624
RACC.....	64, 124
RACH_CONTROL_PARAMETERS.....	318
Radio Access Capability Update.....	590
Radio Blocks.....	58
<i>Radio Cause</i>	596
Radio Priority.....	230, 350
Radio Status Procedure.....	596
Radio Transaction Identifier Field.....	492
<i>RADIO_PRIORITY</i>	340
RADIO-STATUS.....	624
RADIO-STATUS-message.....	596
RADIUS.....	38, 286
RAI.....	124, 586
Random TLLI.....	130
<i>RBB</i>	388
R-Bit.....	462
RBSN-Bit.....	494
Ready Timer.....	134
Ready Timer / Specific Settings.....	142
READY-State.....	120
<i>Receive_Block_Bitmap</i>	388
Reduced Block Sequence Number Bit.....	494
Relative Reserved Block Period Field.....	456
relay function at the PCU.....	566

Reliability Class	238
Reset.....	690
RESUME.....	626
Resume Procedure	592
RESUME-ACK.....	626
RESUME-ACK-message	592
RESUME-message.....	592
RESUME-NACK	626
RESUME-RETRIES.....	592
Retry Bit	462
RFC 1144	704
RLC / MAC Downlink Control Block.....	444
RLC / MAC Downlink Data Block.....	436
RLC / MAC Uplink Control Block	448
RLC / MAC Uplink Data Block	440
RLC_DATA_BLOCKS_GRANTED.....	368
RLC_MODE.....	340
RLC_OCTET_COUNT.....	340
Routing Area.....	122
Routing Area Identification.....	124
Routing Area Identity	586
RRBP	456
RTI-Field	492
R-Value	576

S

S	318
S/P-Bit.....	454
S1, S2 Bits	666
SAPI.....	584, 664
Service Precedence / Priority	230
SGSN.....	16
SGSN_CT_ACK	182
SGSN_CT_REQ.....	182

SGSN_CT_RSP	182
SGSN-INVOKE-TRACE	632
Short Access	342
SI-Bit.....	406, 464
simple class A mobile station	42
Single Block without TBF Establishment.....	342
SN.....	706
SND	264
SN-DATA PDU	706
SNDTCP	702
SN-PDU.....	702, 706
SNU	264
SN-UNITDATA PDU.....	706
SPLIT_PG_CYCLE	201
SSN	388
SSN for GPRS.....	118
Stall Indicator Bit.....	406, 464
STANDBY-State	120
Starting_Sequence_Number.....	388
STATUS	632
Stealing Flags identify the Coding Scheme.....	106
storage of P-TMSI and RAC.....	130
Sub-Network Service Protocol	520
Subsystem Numbers for GPRS.....	118
Supplementary / Polling Bit	454
SUSPEND	626
Suspend Procedure.....	592
Suspend Reference Number.....	592
SUSPEND-ACK.....	626
SUSPEND-ACK-message.....	592
SUSPEND-message	592
SUSPEND-NACK	626
SUSPEND-RETRIES	592
Suspension Cause	592
SYS_INFO 13 position	64

SYS_INFO13 64, 126

T

T_AVG_T	422
T_AVG_W	422
T1	56, 604
T2	56, 602
T200	678, 688
T3	592
T3'	56
T3141	318
T3146	318
T3164	318
T3166	320, 350
T3168	340
T3169	366, 390
T3170	348
T3180	366
T3182	388, 390, 406
T3186	348
T3190	394, 402
T3191	394
T3192	394
T3193	394
T3195	404
T3212	146
T3310	166
T3312	146
T3314	134
T3321	188
T3330	178
T3350	170, 180
T3360	168, 172
T3370	166

T3380	286
T3385	292
T3390	296
T3395	298, 300
T4	592
T6-1	172
T6-2	172
T8	190
T9	188
TAI	74
Tail Bits	96
TBF	358
TBF_STARTING_TIME	362, 368, 374
T-bit	706
T-Bit	576
Tc	534
TCP/IP Header Compression (⇔ RFC 1144)	30
Temporary Block Flow	358
Temporary Flow Identity	358
Temporary Logical Link Identifier	130
TFI	358
TFI-Field	474
TI	150
TI-Bit	472
TI-flag	150
Timing Advance - Message	78
Timing Advance Control in GSM	74
Timing Advance Control Using Polling	84
Timing Advance Index	74
TI-value	150
TLLI	130, 584
TLLI Indicator Bit	472
Tns-Alive	554
Tns-Reset	548
Tns-Test	554

T_{ra}	50
Transaction Identifier	150
Transmission Rates for CS-1 to CS-4	108
transparent access	254
Transparent Access.....	38
TRAU	6
T_{rb}	50
Triples	166
T_{ta}	50
T_{tb}	50
Two Phase Packet Access	314
Two-Phase Packet Access on CCCH in Detail.....	338
TX_INT.....	318

U

UL-UNITDATA	622
UL-UNITDATA PDU	586
unprotected mode.....	676
UPD_PDP_CT_REQ	184
UPD_PDP_CT_RSP.....	184
Uplink Power Control.....	416
Uplink Resource Allocation.....	360
Uplink State Flag	364, 452
USF	364, 452

USF_GRANULARITY	368
USF-Free-Value	66, 364
USF-Unused-Value	364

V

V(A)	406
V(S).....	406
V.42bis.....	28, 704

W

W1, W2, W3, W4 Bits	684
Wildcard APN	250

Γ_{CH}	420
---------------------	-----

α	420
----------------	-----